



Podwójny interfejs czytnika kart DITEO INGENICO - CARTESAPUCE-DISCOUNT™

Produit	Podwójny interfejs czytnika kart DITEO INGENICO
Résumé	Reader DITEO INGENICO: Mixed PC / SC CCID & Support microprocessor cards contactless ISO 7816 1/4 & contactless ISO 14443 A / B / B 'Innovatron. Public transport is used to audit the contactless card at the counter. Hospitals is used for strong authentication, electronic signature healthcare professional. WHQL certified driver, also available for Mac OS & Linux.
Prix	42.59 EUR
Description	<p>Reader easy to use and ergonomic : • A software package manager is also available, to install and configure the drive very Diteo simply based on the application environment. • The player has Diteo multicolor LED high brightness indicating the connection status to the user and to differentiate the method of use of the reader. • The upper Diteo for receiving the contactless card and includes flanges around the dedicated surface. There is therefore no risk of falling or slipping possible: map arises and repeats a simple, fluid and natural. In addition, thanks to its rubber pads hemispherical drive does not slip on the work plan and has maximum stability. Advantages for the user • The Diteo is an easy to customize with a specific area reserved for affixing a sticker or performance a four-color silkscreen. • The Diteo meets the standards for the respect of the environment and is fully recyclable. PC Interfaces USB 2.0 (USB 1.1 &) full speed. According to CCID driver interface contact driver for the contactless interface (installer supplied) Interface card Mixed interface: ISO / IEC 7816 and ISO / IEC 14443 Multi-protocol 13.56MHz: ISO14443 A / B / B 'and MIFARE Innovatron Speed non-contact transfer: up to 424Kbps (848Kbps optional configurable) Supported Smart Cards ISO 7816 quarter (smart cards). ISO / IEC 14443-4 PICC Type A and Type B / B 'MIFARE (DESFire ...), IAS ECC, Calypso (electronic ticketing). Certifications: USB 2.0 full speed (and USB 1.1), EMV Level 1, Microsoft WHQL, CE / RoHS Supported Environments: Microsoft Windows 2000/XP/Vista 32-64 bit / Seven 32-64 bit, MacOS 10.4 Tiger/10.5 Leopard/10.6 Leopard/10.7 Snow Lion, Linux, Size 111 x 81 x 16 mm Weight 133 g. Download drivers and pilots</p>
Référence	DITEO

Image produit

